

Indore Navigation position using Open Street Map (OSM)

Shaik Heena¹, B. Sonia², Dr. M.L.S.N.S.Lakshmi³, L. Eswaramma⁴, Shaik Asif⁵

^{1 2 4 5} Department of Computer Science and Engineering

³ Dept Of Electronics and Communication Electronics

^{1,2,3, 4,5} QIS College of Engineering and Technology, Ongole, Andhra Pradesh, India

¹heena.sk@qiscet.edu.in, ²sonia.b@qiscet.edu.in, ³lakshmi.m@qiscet.edu.in,

⁴eswaramma.l@qiscet.edu.in, ⁵asif.sk@qiscet.edu.in

Corresponding Author Mail: qispublications@qiscet.edu.in

Article Info

Page Number: 176-181

Publication Issue:

Vol 69 No. 1 (2020)

Article Received: 10 August 2020

Revised: 15 September 2020

Accepted: 20 October 2020

Publication: 25 November 2020

Abstract

The suggested system is a practical aid for navigating a university area. It might be challenging for parents and guests to explore unfamiliar or new regions on their own. As a result, the suggested strategy will assist students in navigating the campus as we have chosen this location for our research. Our present goal is to create a system that would let a visitor explore parts of the campus that are foreign to him. Additionally, the suggested system would display information on events, circulars, and other things.

1. Introduction

Setting up the user's position correctly and then showing directions to guide them through feasible routes to their intended destination is known as navigation. The most common and widely used satellite navigation system is the global Positioning System (GPS). All ships and almost all aeroplanes utilize some form of GPS technology. It is a chronological framework with placement possibilities for uncontrollable external factors. While GPS does not provide the accurate location within any large residences, such as airports, hospitals, office buildings, large institutions, and so on. With the aid of the beacon sensor, our system will offer precise localized navigation throughout a sizable institute. One of the management frames in IEEE 802.11-based WLANs is the beacon body. It includes every piece of information concerning. Beacon messages are exchanged between stations in the IBSS network. We recommend the quickest path from the supply option location. We also employ the sound tag for clear communication and improved user experience for the exit user. They adjust the indoor positioning algorithm for the indoor map framework and also make advantage of map data access. This access enables open access to indoor map data and may be used for a variety of tasks, including displaying maps and objects as well as other tasks like upgrading the functionality of placed items, separating positioning modules with a common interface, and setting sensors. Outside of maps, it now involves the calculation of integrated outdoor and indoor routes and the provision of positional correction information in a bundled and customizable framework. Many methods for creating an indoor map rely on sensor platforms to gather the geometry of an indoor area, such as the ROS-implemented octet map library and Horning. It includes amazing placement, rendering, navigation, and unique visualizations in a

module with cross-platform support. With the developed framework, new projects can be covered without having to duplicate old ones.

2. Attached Foundation Work

Thomas Gretchen [1] proposed a method titled "A map framework using crowd-source data for indoor positioning and navigation," which presents a framework for indoor positioning and navigation made possible by the use of open street map (OSM) for rendering admirable indoor and outdoor maps and in addition they calculate the navigation routers. A recommended tactic was kunggeharoen kamphaeng [2] "Development of GPS-Based navigation for Kasetsart University, Kamahis seen campus." Visitors who are tourists or official receivers may have difficulties like confusion and delays due to the size and diversity of a college campus like the one at Kasetsart University. Thomas Gretchen [1] proposed a technique named "A map framework leveraging crowd-source data for indoor location and navigation. "It gives a framework for interior positioning and navigation made possible by the usage of open street map (OSM), which is utilized to produce beautiful indoor and outdoor maps and also figures out the navigation routers. The kunggeharoen kamphaeng [2], the main reason for that is to expand the integration of POI with a GPS-based navigation system (factor of interest) database of the campus's sites and areas. A network application for phones that runs on web browsers was created to accomplish this. The system consists of a module called Map Configuration that connects to an application using the Google Map APIs to display maps. Detailed Location Information Building a method that makes use of java variables connected to the object's present coordinates and destination location is the initial stage in these processes. As part of the process of creating a database to gather position coordinates for storing that information in a MySQL database, they programmed with PHP, AJAX, Java, and JavaScript utilizing the core concepts of GPS technology. Analysis of Systems

Existing System:

There are a lot of smartphone apps available, but they are only ever made with one of two purposes in mind: navigation or information delivery. Installing numerous apps is not ideal if we want information about upcoming events.

Proposed System:

As a component of the proposed system, we are creating a programme that can be used for communication and navigation as well as to share data on a variety of events occurring in institutions. There is just one app that can instruct pupils while directing inexperienced instructors, students, parents, and visitors. No need to download numerous applications.

3. METHODOLOGY

Finding my way. Six way finding trials made up the real-world way finding assignment, and each trial's difficulty was determined by the amount of goals, the number of streets to be travelled, and the distance between each goal. Each endeavor had a unique beginning and necessitated research on a variety of street networks in the regions south of the British

Museum in London's Covent Garden and the Montparnasse cemetery in Paris. To reduce traffic, we chose routes that were less congested and made sure the participants were unfamiliar with them. Prior to each trial, participants were given a map that only displayed the facing direction, the neighborhood's street network, and the positions of the targets. An iPad MP24B/A tablet (9.7 inches) was used to display the maps. Doors and gates with distinctive characteristics were the targets (e.g. specific color, size, or material). For as long as one minute, participants had to memorize the map. They were instructed to find the goals after the allotted minute had expired and the map was taken away. For navigational purposes, they were given color photographs of the target. To calibrate the time limit for each route, we ran pilot tests with 3 participants in London and 2 people in Paris—participants who were not utilized in the analyses. We set these time limitations so that we could make a few errors while still moving along at a respectable speed. According to preliminary research, participants would probably be guessing if they needed more time than this. And had forgotten the street layout or the goals' locations. We multiplied this distance by the participant's overall goal total plus one in order to accommodate for those individuals who did not finish all routes. To address situations in which a participant failed to achieve any goals, we added 1. (This only happened once). This distance, which we aggregate over Routes 1 through 6, is known as the metric normalized distance. Participants were informed by the experimenter if they crossed the boundaries of the defined zone depicted on the map they had viewed. Claimed they needed to turn around since they had reached the limit of the search area. Routes 1 and 2 in London take six minutes each, Routes 3 and 4 each take six minutes, while Routes 5 and 6 each take twelve minutes. Paris's Route One takes five minutes, whereas Route Two, Route Three, Route Four, Route Five, and Route Six take eight, nine, sixteen, and twenty respectively.

The experimenter's smartphone GPS was used to record the coordinates of the subjects' trajectories at $F_s = 1$ Hz. We visually analyzed each GPS track to handle potential signal loss. We used linear interpolation to fill in the gaps between the first and last missing points for signal losses where the participant did not turn at all. When the participant changed lanes during the signal loss, we destroyed the data, making it difficult for us to recreate the path (5 trials out of 180 in Paris, 6 out of 180 in London). Each route's Euclidean distance served as a performance gauge (in meters).

Path Integration. Four path integration trials, each with a different number of turns and a different difficulty level, made up the real-world path integration job. The familiarity effect was avoided by choosing path integration pathways that did not overlap any way finding routes. Participants received instructions to follow the researcher to an endpoint, where they were asked to indicate back toward the starting point, and were notified when they had reached at the experiment's commencement point. We correctly recorded the direction using a numerical compass. Performance was defined as the reciprocal of the angle, expressed in degrees, between the participant-indicated direction and the actual situation as it existed on the ground. The angles of the path integration error's absolute values were added after that.

Conclusion

A thorough survey is conducted, and the results are shown in Table 1. Using OSM and the Robot operating system, the technique [1] offers indoor positioning, which enables precise location inside the building. In comparison to other methods, it is more economical. The alternative method relies on the magnetic field inside the structure for interior location, but it is more expensive and suffers from performance degradation as the weather changes.

REFERENCES

1. Maguire EA, Burgess N, Donnett JG, Frackowiak RS, Frith CD, O'keefe J. Knowing where and getting there: a human navigation network. *Science*. 1998; 280(5365):921–924. PMID:9572740
2. Pine DS, Grun J, Maguire EA, Burgess N, Zarahn E, Koda V, et al. Neurodevelopmental aspects of spatial navigation: a virtual reality fMRI study. *Neuroimaging*. 2002; 15(2):396–406. PMID: 11798274
3. Epstein RA, Patai EZ, Julian JB, Spiers HJ. The cognitive map in humans: spatial navigation and beyond. *Nature neuroscience*. 2017; 20(11):1504–1513. PMID:29073650
4. Ekstrom AD, Spiers HJ, Bohbot VD, Rosenbaum RS. *Human Spatial Navigation*. Princeton University Press; 2018.
5. Mitolo M, Gardini S, Caffarra P, Ronconi L, Venneri A, Pazzaglia F. Relationship between spatial ability, visuospatial working memory and self-assessed spatial orientation ability: a study in older adults. *Cognitive Processing*. 2015; 16(2):165–176. PMID:25739724
6. Lokka IE, Çöltekin A, Wiener J, Fabrikant SI, Röcke C. Virtual environments as memory training devices in navigational tasks for older adults. *Scientific Reports*. 2018; 8(10809):1–15.
7. Moffat SD, Zondervan AB, Ransack SM. Age differences in spatial memory in a virtual environment navigation task. *Neurobiology of Aging*. 2001; 22:787–796. PMID:11705638
8. Tu S, Wong S, Hodges JR, Irish M, Piguet O, Hornberger M. Lost in spatial translation—A novel tool to objectively assess spatial disorientation in Alzheimer's disease and frontotemporal dementia. *Cortex*. 2015; 67:83–94. PMID:25913063
9. Tsai HyS, Shillair R, Cotten SR, Winstead V, Yost E. Getting grandma online: are tablets the answer for increasing digital inclusion for older adults in the US? *Educational Gerontology*. 2015; 41(10):695–709. PMID:26877583
10. Ruggeri K, Maguire Á, Andrews JL, Martin E, Menon S. Are we there yet? Exploring the impact of translating cognitive tests for dementia using mobile technology in an aging population. *Frontiers in aging neuroscience*. 2016; 8:21. PMID:27014053
11. Mallet KH, Shamloul RM, Corbett D, Finestone HM, Hatcher S, Lumsden J, et al. Recovernow: Feasibility of a mobile tablet-based rehabilitation intervention to treat post-stroke communication deficits in the acute care setting. *PloS one*. 2016; 11(12):e0167950. PMID:28002479
12. Areán PA, Ly KH, Andersson G. Mobile technology for mental health assessment. *Dialogues in clinical neuroscience*. 2016; 18(2):163. PMID:27489456

13. Ashford, J. W., Borson, S., O'Hara, R., Dash, P., Frank, L., Robert, P., et al. (2007). Should older adults be screened for dementia? It is important to screen for evidence of dementia! *Alzheimers Dement.* 3, 75–80. doi: 10.1016/j.jalz.2007.03.005
14. Bauer, R. M., Iverson, G. L., Cernich, A. N., Binder, L. M., Ruff, R. M., and Naugle, R. I. (2012). Computerised neuropsychological assessment devices: joint position paper of the American academy of clinical neuropsychology and the national academy of neuropsychology. *Clin. Neuropsychol.* 26, 177–196. doi: 10.1080/13854046.2012.663001
15. Chee, M. W., O'Craven, K. M., Bergida, R., Rosen, B. R., and Savoy, R. L. (1999). Auditory and visual word processing studied with fMRI. *Hum. Brain Mapp.* 7, 15–28. doi: 10.1002/(SICI)1097-0193(1999)7:1<15::AID-HBM2>3.0.CO;2-6
16. Couteur, D. G., Le Doust, J., Creasey, H., and Brayne, C. (2013). Political drive to screen for pre-dementia: not evidence based and ignores the harms of diagnosis. *BMJ* 347:f5125. doi: 10.1136/bmj.f5125
17. Cullen, B., O'Neill, B., Evans, J. J., Coen, R. F., and Lawlor, B. A. (2007). A review of screening tests for cognitive impairment. *J. Neurol. Neurosurg. Psychiatr.* 78, 790–799. doi: 10.1136/jnnp.2006.095414
18. Czaja, S. J., Charness, N., Fisk, A. D., Hertzog, C., Nair, S. N., Rogers, W. A., et al. (2006). Factors predicting the use of technology: findings from the Center for Research and Education on Aging and Technology Enhancement (CREATE). *Psychol. Aging* 21, 333–352. doi: 10.1037/0882-7974.21.2.333
19. Destrieux, C., Hommet, C., Domengie, F., Boissy, J.-M., De Marco, G., Joannette, Y., et al. (2012). Influence of age on the dynamics of fMRI activations during a semantic fluency task. *J. Neuroradiol.* 39, 158–166. doi: 10.1016/j.neurad.2011.05.005
20. Di Rosa, E., Hannigan, C., Brennan, S., Reilly, R., Rapcan, V., and Robertson, I. H. (2014). Reliability and validity of the Automatic Cognitive Assessment Delivery (ACAD). *Front. Aging Neurosci.* 6:34. doi: 10.3389/fnagi.2014.00034
21. Dillon, A. (1992). Reading from paper versus screens: a critical review of the empirical literature. *Ergonomics* 35, 1297–1326. doi: 10.1080/00140139208967394
22. Errey, C., Ginns, P., and Pitts, C. (2006). Cognitive Load Theory and User Interface Design: Making Software Easy to Use. The Performance Technologies Group Pty Ltd. Available online at: <http://bit.ly/1EBLKVV>
23. Farrington, C., Aristidou, A., and Ruggeri, K. (2014). mHealth and global mental health: still waiting for the mH2 wedding? *Global Health* 10, 17–25. doi: 10.1186/1744-8603-10-17
24. Feliciano, L., Horning, S. M., Klebe, K. J., Anderson, S. L., Cornwell, R. E., and Davis, H. P. (2013). Utility of the SLUMS as a cognitive screening tool among a nonveteran sample of older adults. *Am. J. Geriatr. Psychiatry* 21, 623–630. doi: 10.1016/j.jagp.2013.01.024
25. Fox, C., Lafortune, L., Boustani, M., Dening, T., Rait, G., and Brayne, C. (2013). Screening for dementia - is it a no brainer? *Int. J. Clin. Pract.* 67, 1076–1080. doi: 10.1111/ijcp.12239
26. Galitz, W. O. (2007). *The Essential Guide to User Interface Design: An Introduction to GUI Design Principles and Techniques*, 3rd Edn. Indianapolis, IN: John Wiley & Sons.

27. Gates, N. J., and Kochan, N. A. (2015). Computerised and on-line neuropsychological testing for late-life cognition and neurocognitive disorders: are we there yet? *Curr. Opin. Psychiatry* 28, 165–172. doi: 10.1097/YCO.0000000000000141.
28. P Ramprakash, M Sakthivadivel, N Krishnaraj, J Ramprasath. "Host-based Intrusion Detection System using Sequence of System Calls" *International Journal of Engineering and Management Research*, Vandana Publications, Volume 4, Issue 2, 241-247, 2014
29. N Krishnaraj, S Smys."A multihoming ACO-MDV routing for maximum power efficiency in an IoT environment" *Wireless Personal Communications* 109 (1), 243-256, 2019.
30. N Krishnaraj, R Bhuvanesh Kumar, D Rajeshwar, T Sanjay Kumar, Implementation of energy aware modified distance vector routing protocol for energy efficiency in wireless sensor networks, 2020 International Conference on Inventive Computation Technologies (ICICT),201-204
31. Ibrahim, S. Jafar Ali, and M. Thangamani. "Enhanced singular value decomposition for prediction of drugs and diseases with hepatocellular carcinoma based on multi-source bat algorithm based random walk." *Measurement* 141 (2019): 176-183. <https://doi.org/10.1016/j.measurement.2019.02.056>
32. Ibrahim, Jafar Ali S., S. Rajasekar, Varsha, M. Karunakaran, K. Kasirajan, Kalyan NS Chakravarthy, V. Kumar, and K. J. Kaur. "Recent advances in performance and effect of Zr doping with ZnO thin film sensor in ammonia vapour sensing." *GLOBAL NEST JOURNAL* 23, no. 4 (2021): 526-531. <https://doi.org/10.30955/gnj.004020> , https://journal.gnest.org/publication/gnest_04020
33. N.S. Kalyan Chakravarthy, B. Karthikeyan, K. Alhaf Malik, D.Bujji Babbu., K. Nithya S.Jafar Ali Ibrahim , Survey of Cooperative Routing Algorithms in Wireless Sensor Networks, *Journal of Annals of the Romanian Society for Cell Biology* ,5316-5320, 2021
34. Rajmohan, G, Chinnappan, CV, John William, AD, Chandrakrishnan Balakrishnan, S, Anand Muthu, B, Manogaran, G. Revamping land coverage analysis using aerial satellite image mapping. *Trans Emerging Tel Tech.* 2021; 32:e3927. <https://doi.org/10.1002/ett.3927>
35. Vignesh, C.C., Sivaparthipan, C.B., Daniel, J.A. et al. Adjacent Node based Energetic Association Factor Routing Protocol in Wireless Sensor Networks. *Wireless Pers Commun* 119, 3255–3270 (2021). <https://doi.org/10.1007/s11277-021-08397-0>.
36. C Chandru Vignesh, S Karthik, Predicting the position of adjacent nodes with QoS in mobile ad hoc networks, *Journal of Multimedia Tools and Applications*, Springer US, Vol 79, 8445-8457,2020